

AP00.20-U-1208JAB SERVICE SHEET for Mercedes-Benz Maintenance System (USA) 8.2.05

MODEL 215

AMG models and CL600

Passenger cars Model Year 2006



Customer: Repair order number:						
First visit	at 1,000 - 3,000 miles		Performed	YES	NO	
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals		Tires rotated	YES	NO	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure		Tires inspecte	ted YES NO		
Current mileage reading: Oil grade/viscosity: Additional notes:						
Service work to be performed as advised by Completion date: Confirm work has been performed by signing below:						
1st A service at 10,000 miles or 1 year, then every 20,000 miles or 2 years 1st B service at 20,000 miles or 2 years, then every 20,000 miles or 2 years						
Determine "Additional Work" needed, if any. Refer to "Additional work" section (check if applicable)						
at approx. every:	40,000 mi or 4 years 50,000 mi or 4 years 60,000 mi or 4 years 60,000 mi or 5 years 100,000 mi or 5 years 150,000 mi or 15 years		every: once at:	2 years 3 years 5 years 40,000 mi 150,000 mi		

i See last page for "Additional Work".

Additional flat rates apply for procedures marked with FAP

Completed ⊠		A-Service	O B-Service	Not OK	
<u> </u>		↓	↓	1	
	Interior				
	Reset maintenance counter in instrument cluster	×	\otimes		AP00.20-P-0042M
	Replace dust filter (if equipped)		\otimes		AP83.00-P-8381MA
	Function check				
	Horn, headlamp flasher, hazard warning flasher, turn signal indicators	\boxtimes	\otimes		
	Warning/indicator lamps, illumination and interior lighting	X	\otimes		
	Front and rear lamps	X	\otimes		
	Windshield wipers, windshield washer system	X	\otimes		AP82.35-P-8252BA
	Headlamp cleaning system	X	\otimes		
	Check seat belts for damage and proper function		\otimes		AP91.40-P-9150M
	Check parking brake (function test only)		\otimes		AP42.00-P-4290BA
	Wheels, brakes				
	Remove and mount wheels		\otimes		AP40.10-P-4050Z
	Check front brake pads for lining thickness (remove 1 front wheel)	\boxtimes			AP42.10-P-4251I
	Check brake pads for lining thickness front/rear		\otimes		AP42.10-P-4251I
	Check condition/thickness of brake discs front/rear		\otimes		AP42.10-P-4251I
	Inspect tires for damage and condition	\boxtimes	\otimes		AP40.10-P-4051Z
	Measure tread depth, enter in mm: LF RF LR RR outside		⊗		AP40.10-P-4051Z
	Correct tire inflation pressure	\boxtimes	\otimes		
	Underside of vehicle				
	Leakage - Major components Check for chafe marks, line routing, dama-		\otimes		AP00.20-P-0053BA
	ged components iln the event of leakage, determine cause and perform repair via separate work order				
	CL600 / CL65 AMG		\otimes		AP00.20-P-0053H
	Check condition of front axle ball joints and rubber boots		\otimes		AP33.20-P-3353BA
	Check condition of steering mechanical components and rubber boots		8		AP46.00-P-4653F

Completed 2		A-Service	O B-Service	Not OK	
,		<u> </u>	↓	<u> </u>	
	Engine compartment				
	Leakage - Major components Check for chafe marks, line routing, damaged components in the event of leakage, determine cause and perform repair via separate work order		⊗		AP00.20-P-0053BA
	CL600 / CL65 AMG		\otimes		AP00.20-P-0053H
	Check condition of poly-V-belt		\otimes		AP13.22-P-1351Z
	Engine 275		\otimes		AP13.22-P-1351L
	Check catch, safety catch and hinges on engine hood for proper operation.	\boxtimes	\otimes		AP88.40-P-8851M
	Engine oil and filter change	\boxtimes	\otimes		AP18.00-P-0101R
	Engine 275	X	\otimes		AP18.00-P-0101H
	Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order				
	Engine cooling system, antifreeze and corrosion protection (Engine 275 main circuit)	×	\otimes		AP20.00-P-2010H
	Brake system	X	\otimes		AP42.10-P-4210Z
	Power steering		\otimes		AP46.00-P-4611N
	Active Body Control		\otimes		AP32.50-P-3213I
	Windshield washer system (incl. summer/winter cleanser)	X	\otimes		AP82.35-P-8210N
identi	Vehicle front/rear				
	Check and correct headlamp setting		\otimes		AP82.10-P-8260M
	Check wiper blade condition	X	\otimes		AP82.30-P-8253G
	Trunk				
	Correct tire inflation pressure in spare tire	\boxtimes	\otimes		
	Check trunk lighting	X	\otimes		
	Battery, check battery condition using "Midtronics MCR 717" Tester	×	\otimes		AP54.10-U-5453A
	Additional Work				
Completed ⊠	Perform:	Yes		Not OK	
↓	Ou 40 000	1		\	
l San	Once at 40,000 mi:				A D 27 O O D 27 O 21
₩ AP	Automatic transmission - oil and filter change				AP27.00-P-2702I

	Completed ⊠	Perforr	n: Yes ↓	Not OK ↓	
	•	At approx. every 40,000 mi or 4 years:	•	•	
₩AP		Replace air cleaner filter element (Engine 113)			
⊯AP		Replace poly-V-belt tensioning device (Engine 275)			AP13.25-P-1382H
₩AP		Replace compressor poly-V-belt (Engine 113)			AP13.22-P-1381R
		At approx. every 50,000 mi or 4 years:			
⊯ÃΡ		Check condition of driveshaft flex discs			AP41.10-P-4152Z
		At approx. every 60,000 mi or 4 years:			
₩AP		Replace air cleaner filter element (Engine 275)			AP09.10-P-0980H
		At approx. every 60,000 mi or 5 years:			
₩AP		Replace activated charcoal filter (if equipped)			AP83.00-P-8382M
⊯°AΡ		Replace fuel filter (Engine 113)			AP47.20-P-0780DC
⊯°AΡ		Replace fuel filter (Engine 275)			AP47.20-P-0780L
⊯ÃΡ		Replace spark plugs (Engine 275)			AP15.10-P-1580L
		At approx. every 100,000 mi or 5 years:			
⊯ÃΡ		Replace spark plugs (Engine 113)			AP15.10-P-1580AB
		At approx. every 150,000 mi or 15 years:			
⊯°AP		Engine 113: Replace coolant (water/anticorrosion/antifreeze mixture)			AP20.00-P-2080DA
₩ÃΡ		Engine 275: Replace coolant for low tem- perature circuit (water/anticorrosion/ antifreeze mixture)			AP20.00-P-2080H
		Every 2 years:			
₩ÃΡ		Replace brake fluid			AP42.00-P-4280BA
₩AP		Check body paint damage by service advisor			AP98.00-P-9850BA
β≆AP		Check chassis and supporting body parts for damage and corrosion by service advisor			AP00.20-P-0090BA
		Every 3 years:			
₩ÃΡ		Engine 275: Replace coolant for main circuit (water/anticorrosion/antifreeze mixt re)	□ u-		AP20.00-P-2080H
		Every 5 years:			
FAP		Tilt/sliding roof: clean sliding rails and sliders			AP77.20-P-7731A

	Completed ⊠	Perform:	Yes	Not OK	
	↓		↓	\	
		Vehicle over 150,000 mi:			
		Check if all fluid levels and changes are updated			
F⇔AP		Transmission			
F≆AP		Rear axle			
		Check if air, fuel, ventilation filters are updated			
⊯AP		Engine air filter			
FAP		Fuel filter			
F⇔AP		Dust filter (if applicable)			
F⇔AP		Activated charcoal filter (if applicable)			
		Check integrity of engine, mechanical comonents			
⊯AP		Perform compression test (hot and cold) Refer to BE01.00-Z-9999AZ			
₩FAP		Perform leak down test (hot and cold)			AP00.20-P-0053BA
		CL600 / CL65 AMG			AP00.20-P-0053H
₩FAP		Check spark plugs			
₩FAP		Exhaust system hangers and leaks			
		Check damaged / worn drivetrain parts			
₩ŶΑP		Front wheel bearing play			
₩ŶΑP		Rear wheel bearing play			
F≆AP		Axle joint play			
F⇔AP		Flexible disks			
F≆AP		Tie rod and drag link joints			