

Service

AP00.20-U-1208L 04.06.04 Service Sheet for Mercedes-Benz Maintenance System (USA)

except AMG models and SL600 MODEL 230

Passenger Cars Model Year 2005

USA



Customer:		Repair order nu	Repair order number:				
First visit	at 1,000 - 3,000 miles	Performed	YES		NO]	
Tire Rotation (non-staggered width wheel setup only)	Performed in accordance wit manufacturer's recommende		YES		NO]	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and tire inflation pressure	correct Tires inspec	ted YES		NO]	
Current mileage reading: _		Oil grade/viscos	sity:				
Additional notes:							
Service work to be perform service advisor:	ed as advised by C	ompletion date	Confirm w		n performed	 by	
•	ed as advised by C	ompletion date			n performed	by	
1st A service at 13,00	ed as advised by Comparison of the control of the c	26,000 miles or 2 year	signing be		n performed	bby	
1st A service at 13,00 1st B service at 26,00	0 miles or 1 year, then every	26,000 miles or 2 year ry 26,000 miles or 2 yea	signing be		n performed	by	
1st A service at 13,00 1st B service at 26,00 Determine "Additiona (check if applicable)	0 miles or 1 year, then every 0 miles or 2 years, then ever l work" needed, if any. Refer	26,000 miles or 2 year ry 26,000 miles or 2 year to "Additional Work" s	signing be	low:	n performed	by	
1st A service at 13,00 1st B service at 26,00 Determine "Additiona (check if applicable) once at first service at:	0 miles or 1 year, then every 0 miles or 2 years, then every 1 work" needed, if any. Refer	26,000 miles or 2 year ry 26,000 miles or 2 yea	signing be s ars section	low:	n performed	bby	
1st A service at 13,00 1st B service at 26,00 Determine "Additiona (check if applicable)	0 miles or 1 year, then every 0 miles or 2 years, then every 1 work" needed, if any. Refer 13,000 mi or 1 year 52,000 mi or 4 years	26,000 miles or 2 year ry 26,000 miles or 2 year to "Additional Work" s	signing be s ars section	low:	en performed	by	
1st A service at 13,00 1st B service at 26,00 Determine "Additiona (check if applicable) once at first service at:	0 miles or 1 year, then every 0 miles or 2 years, then every 1 work" needed, if any. Refer 13,000 mi or 1 year 52,000 mi or 4 years 52,000 mi or 5 years	26,000 miles or 2 year ry 26,000 miles or 2 year to "Additional Work" s	signing be s ars section	low:	en performed	by	
1st A service at 13,00 1st B service at 26,00 Determine "Additiona (check if applicable) once at first service at:	0 miles or 1 year, then every 0 miles or 2 years, then every 1 work" needed, if any. Refer 13,000 mi or 1 year 52,000 mi or 4 years	26,000 miles or 2 year ry 26,000 miles or 2 year to "Additional Work" s	signing be s ars section	low:	en performed	by	

completed	¥	A-Service	□ ↓	O B-Service	Not O.K	
		Interior				
The state of the s		Reset maintenance counter in instrument cluster	X	\otimes		AP00.20-P-0042M
		Replace combination filter		\otimes		AP83.00-P-8384R
		Function check				
		Warning/indicator lamps, illumination and interior lighting	X	\otimes		
		Windshield wiper/washer system, where applicable: rear window wiper/washer system		⊗		AP82.30-P-8252BA
		Headlamp cleaning system	X	\otimes		
		Check seat belts for damage and proper function		\otimes		AP91.40-P-9150M
		Check Sensotronic Brake Control (SBC) hydraulic unit	X	\otimes		AP42.50-P-4259A
		Check parking brake (function test only)		\otimes		AP42.00-P-4290R
		Wheels, brakes				
		Check front brake pads for lining thickness (remove 1 front wheel)	\boxtimes			AP42.10-P-4251R
		Check brake pads for lining thickness front/rear		\otimes		AP42.10-P-4251R
		Check condition of brake discs front/rear		\otimes		AP42.10-P-4251R
		Correct tire inflation pressure	\boxtimes	\otimes		
		Inspect tires for damage and condition	\boxtimes	\otimes		AP40.10-P-4051Z
		Measure tread depth, enter in mm:		\otimes		AP40.10-P-4051Z
		LF RF LR RR outside				
		Underside of vehicle				
		Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		⊗		AP00.20-P-0053BA

completed	⊠ 	A-Service	; □ ↓	O B-Service ↓	Not O.F	ζ.
		Check condition of front axle ball joints and rubber boots		8		AP33.20-P-3353BA
		Check condition of steering's mechanical components and rubber boots		8		AP46.00-P-4653F
		Engine compartment				
		Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		8		AP00.20-P-0053BA
		Check condition of poly-V-belt		\otimes		AP13.22-P-1351Z
		Check catch, safety catch and hinges of engine hood for proper operation. Replace components with even the slightest malfunction.	☒	8		AP88.40-P-8851R
		Engine oil and filter change	\boxtimes	\otimes		AP18.00-P-0101AF
		Check and correct fluid level If there is a loss of fluid, determine cause and perform repair via separate work or				
		Engine cooling system, antifreeze and corrosion protection	X	\otimes		AP20.00-P-2010Z
		Brake system	X	\otimes		AP42.10-P-4210Z
		Battery, check and correct fluid level; check battery condition using "Midtronics MCR 717" tester	X	⊗		AP54.10-U-5453A
		Power steering with Active body Control Code 487a		8		AP46.00-P-4611N
		without Active body Control Code 487a		\otimes		AP46.00-P-4611BB
		Active Body Control		\otimes		AP32.50-P-3213I
		Windshield washer system	X	\otimes		AP82.35-P-8210N
		Trunk				
		Battery, check battery condition using "Midtronics MCR 717" tester	\boxtimes	8		AP54.10-U-5453A
		Check TIREFIT tire sealant expiration date	\boxtimes	8		AP40.10-P-4054R

comp	oleted ⊠ ↓	Additional Work Perform:	Yes ↓	Not O.K. ↓
r≆ AP		Once at first service at 13,000 miles or 1 year Parking brake - Adjust cable slack	ar	☐ AP42.20-P-4262R
		At approx. every 52,000 mi or 4 years:		
F AP		Check condition of driveshafts flex discs		AP41.10-P-4152Z
I≆ AP		Replace air cleaner filter element		
		At approx. every 52,000 mi or 5 years:		
r≆ AP		Replace activated charcoal filter (if equipped)		AP83.00-P-8382M
		At approx. every 65,000 mi or 5 years:		
p≅ AP		Replace fuel filter		AP47.20-P-0780DC
		At approx. every 143,000 mi or 15 years:		
p≆ AP		Replace coolant (water/anticorrosion/antifreeze)		AP20.00-P-2080DA
		Replace spark plugs		
I⊯ AP		At approx. every 91,000 mi or 5 years:		AP15.10-P-1580AB
		Every 2 years:		
p≆ AP		Replace brake fluid Prior to replacing brake fluid perform the following checks via STAR DIAGNOSIS SYSTEM (SDS): 1 - Check pretension pressure of Sensotron Brake Control (SBC) pressure reservoir 2 - Check operating time of Sensotronic Brake Control (SBC) unit	ic	AP42.00-P-4280R
r≆ AP		Check chassis and supporting body parts for damage and corrision by Service Advisor		☐ AP00.20-P-0090BA
p≆ AP		Check body for paint damage by service Advisor		☐ AP98.00-P-9850BA

completed	× ↓	Perform:	Yes ↓	Not O.K. ↓
		Vehicle over 143,000 mi:		
		Check if all fluid levels and changes are updated		
r≆ AP		Transmission		
r≆ AP		Rear axle		
r≆ AP		Front axle (if applicable)		
I≆ AP		Transfer case (if applicable)		
		Check if air, fuel, ventilation filters are updated		
r≆ AP		Engine air filter		
r≆ AP		Fuel filter		
r≆ AP		Combination / dust filter (if applicable)		
I≆ AP		Activated charcoal filter (if applicable)		
		Check integrity of engine, mechanical components		
r≆ AP		Perform compression test (hot and cold)		☐ BE01.00-Z-9999AZ
r≆ AP		Perform leak down test (hot and cold)		☐ AP00.20-P-0053BA
r≆ AP		Check spark plugs		
I≈ AP		Exhaust system hangers and leaks		
		Check damaged / worn drivetrain parts		
I≆ AP		Front wheel bearings play		
r≆ AP		Rear wheel bearings play		
r≆ AP		Axles joints play		
I≆ AP		Flexible discs		
r≆ AP		Tie rod and drag link joints		
i e				