

AP00.20-U-1208VD SERVICE SHEET for Mercedes-Benz Maintenance System (USA) 28.3.07

MODEL 171

except AMG models

Passenger cars Model Year 2008





Customer:	Repair order number:			
First visit	at 1,000 - 3,000 miles	Performed	YES	NO
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES	NO
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES	NO
Current mileage reading: Additional notes:			r:	
Service work to be performed as advised by Completion date: Confirm work has been performed by signing below:				

i

US Service 4 through US Service 20 apply to "Additional work" items only.

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2.

Perform each service as described.

US Service		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
1	US Service	first at 26,000 mi or 2 years;	after first every 26,000 mi or 2 years	
	2		Not OK	
1	<u> </u>	Engine compartment	<u> </u>	
		Engine compartment		
	0	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053V
	0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851V
	0	Check condition of poly-V-belt		
		Check fluid level, correct as required ilf there is a loss of fluid, determine cause and perform repair via separate work order		
	0	Battery, check and correct fluid level		AP54.10-P-5410V
	0	Battery, check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.		
	0	Brake system		AP42.10-P-4210V
	0	Power steering		AP46.00-P-4611V
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210N
600		Interior		
	0	Reset service indicator in instrument cluster Function test		AP00.20-P-0042V
	\circ	Check parking brake (function test only)		
	0	Horn		
	0	Warning/indicator lamps, illumination and		AP54.30-P-5452C
	_	interior lighting		A1 34.30-1 -3432C
	O	Windshield wipers, windshield washer system, headlamp cleaning system		AP82.30-P-8252V
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150V
		Wheels, brakes		
	' 0	Inspect tires for damage and splits, measure tread depth, record in mm: LF RF LR RR outside		AP40.10-P-4051Z
	0	Check thickness of brake pads, front and rear		AP42.10-P-4253A
	0	Correct tire inflation pressure and enter in bar or psi. LF RF LR RR bar/psi:		

US Service US Service		ice		Not OK	
1		2			
*		<u> </u>	Underside of vehicle	<u> </u>	
en	3		Underside of Venicle		
		\cap	Leakage - Major components		AP00.20-P-0053V
-	•	_	Check for chafe marks, line routing, dama-		711 00.20 1 0033 1
			ged components		
			i In the event of leakage, determine cau-		
			se and perform repair via separate work or- der		
		0	Check front axle ball joints for play, check		AP33.20-P-3353V
		•	rubber boots	_	
		0	Inspect condition of driveshaft flexible		AP41.10-P-4152V
			discs		
		0	Inspect play of tie rod and and drag link		AP46.00-P-4653V
	~ ~		joints, inspect rubber boots		
en (Trunk		
П		0	Check trunk lighting		
1		_	Vehicle front/rear		
lence					
		0	Check wiper blade condition		AP82.30-P-8253G
		0	Check and correct headlamp setting		AP82.10-P-8260V
Co	mpleted	IX		Not OK	
		↓		↓	
US Ser	vice 3		every 13,000 mi or 1 year:		
			Engine compartment		
			Engine - oil and filter change		AP18.00-P-0101VA
US Ser	vice 4		every 2 years:		
			Check bodywork for paint work damage		AP98.00-P-9850BA
			by service advisor		
		_	Underside of vehicle	_	
		Ш	Chassis and load-bearing body components: Check for damage and corrosion	Ц	AP00.20-P-0090BA
			by service advisor		
			Engine compartment		
			Replace brake fluid		AP42.00-P-4280V
US Ser	vice 5		every 26,000 mi or 2 years:		
			Passenger compartment		
			Replace combination filter		AP83.00-P-8384V
US Servic	e 6 and 7	7	not applicable		
US Ser	vice 8		every 52,000 mi or 4 years:		
			Engine compartment		
			Replace engine air-cleaner insert		AP09.10-P-0980V
US Service	9 and 1	0	not applicable		
US Serv	vice 11		every 143,000 mi or 15 years:		
			Trunk		
			Replace fuel filter		AP47.20-P-0780V
US Serv			every 91,000 mi or 5 years:		
Engin		_	Engine compartment		
		Ш	Replace spark plugs		AP15.10-P-1580VA

Con	npleted $oxtimes$			Not OK	
	1			↓	
US Serv	ice 13	every 143,000 mi or 15 years:			
		Engine compartment			
		Replace coolant			AP20.00-P-2080V
US Service	e 14 - 19	not applicable			
US Serv	ice 20	once at 39,000 mi:			
		Underside of vehicle			
		Automatic transmission - oil and filter change			AP27.00-P-2702W
Com	pleted 🗵	Perfo		Not OK	
	1		↓	<u> </u>	
		Vehicle over 143,000 mi:			
		Check if all fluid levels and changes are udated	ıp-		
⊯FAP		Transmission			
⊯ AP		Rear axle			
		Check if air, fuel, ventilation filters are u dated	p-		
¥°AP		Engine air filter			
⊯≆AP		Fuel filter			
¥°AP		Combination filter			
		Check integrity of engine, mechanical comonents)-		
⊯ AP		Perform compression test (hot and cold) Refer to BE01.00-Z-9999AZ			
⊯≆AP		Perform leak down test (hot and cold)			AP00.20-P-0053V
⊯≆AP		Check spark plugs			
⊯ AP		Exhaust system hangers and leaks			
		Check damaged / worn drivetrain parts			
⊯ AP		Front wheel bearing play			
⊯ AP		Rear wheel bearing play			
⊯AP		Axles joint play			
⊯AP		Driveshaft flexible discs			
I¥ AP		Tie rod and drag link joints			