31.5.00



AP00.20-U-0001K SERVICE SHEET for Flexible Service System (FSS)

MODEL 203

Passenger Cars Model Year 2003

USA/CANADA:

System is also known as "Active Service System (ASSYST)" in the Workshop Information System (WIS)

Model 203



Cus	tomer:		Repair order number:					
Confirm work has been performed by signing below			Type of service					
Technician:			<u> </u>	<u> </u>				
		Determine need for service:	B	A				
	Please define type of service to be pe	rformed here:	· · · · · · · · · · · · · · · · · · ·]				
	Current	odometer reading:						
	B-Service last performed	at mi/km:						
	(Enter 0 if B-Service is performed for f	irst time)						
	Difference	in mi/km:						
		Difference < 14,000 mi	Difference ≥ 14,000 mi					
		22,000 Kill		<u>'</u>				
		A-Service	B-Ser	vice				
	icable)	i/80,000 km or 4 years [every:	2 years				
approx. ev		/96,000 km or 5 years		Spark plugs				
	150,000mi/	/250,000km or 15 years						
Determi If the dis records)		vice: ervice" is less (<) than 14,000 n		ned from Service Book				

Additional flat rates apply for procedures marked with ${\begin{tabular}{l} lackbox{\begin{tabular}{l} lackbox{\begin{tabular} lackbox{\begin{tabular}{l} lackbox{\be$

completed	↓	A-Service	□	○ B-Service	Not O.K. ↓	
		Vehicle passenger compartment				
		Function check				
		Warning/indicator lamps, illumination and interior lighting	\boxtimes	\otimes		
		Windshield wipers, windshield washer system	\boxtimes	\otimes		AP82.35-P-8252BA
		Headlamp cleaning system	\boxtimes	\otimes		
		Check seat belts for damage and proper function		\otimes		AP91.40-P-9150P
		Reset FSS counter in instrument cluster	\boxtimes	\otimes		
		Wheels, brakes			-	
		Check front brake pads for lining thickness (remove 1 front wheel at "A" service)	\boxtimes			AP42.10-P-4251BP
		Check brake pad thickness (front and rear)		\otimes		AP42.10-P-4251BP
		Check condition of brake discs front and rear		\otimes		AP42.10-P-4251BP
		Inspect tires for damage and condition	\boxtimes	\otimes		AP40.10-P-4051Z
		Correct tire inflation pressure	\boxtimes	\otimes		
		Measure tread depth, enter in mm:		\otimes		AP40.10-P-4051Z
		LF RF LR RR				
		outside				
		center				
		inside				
		Vehicle under body				
completed	V ↓	A-Service	\Box	O B-Service	Not O.K.	
		Visual check for		8		AP00.20-P-0053BA
		Leakage - Major components Chafe marks, line routing, components. In the event of leakage, determine cause and perform repair via separate work order.				
		Check condition of front axle ball joints and rubber boots		\otimes		AP33.20-P-3353BP
		Check condition of steering's mechanical components and rubber boots		\otimes		AP46.00-P-4653F

		Engine compartment					
		Visually check Leakage - Major components Chafe marks, line routing, components. In the event of leakage, determine cause and perform repair via separate work order.		8			AP00.20-P-0053BA
		Engine oil and filter change	\boxtimes	\otimes			AP18.00-P-0101AE
		Check and correct fluid level					
		Brake system	\times	\otimes			AP42.10-P-4210Z
		Power steering		\otimes			AP46.00-P-4611P
		Windshield washer	X	\otimes			AP82.35-P-8210P
		If so equipped: Battery, wet cell Check acid level, replenish	\boxtimes	\otimes			AP54.10-P-5410A
		Additionally, check battery condition using "Midtronics MCR 717" Tester	\boxtimes	\otimes			SI54.10-P-0003A
		If so equipped: Battery, AGM/VRLA, with black housing Check battery condition using "Midtronics MCR 717" Tester	X	\otimes			SI54.10-P-0003A
		Check catch, safety catch and hinges on engine hood for proper operation. Replace components with even the slightest malfunction.	×	\otimes			
		Trunk			-		
		Correct tire inflation pressure in spare tire	X	\otimes			
		Additional Work					
complete	ed ⊠ ↓	Perform:	yes ↓			Not O.K. ↓	
		At approx. every 50,000 mi/80,000 km or 4 years:					
₩AP		Check condition of driveshaft flex discs					AP41.10-P-4152Z
		At approx. every 60,000 mi/96,000 km or 4 years:					
₩AP		Replace air cleaner filter element					

	At approx. every 60,000 mi/96,000 km or 5 years:		
	Check condition of poly-V-belt		AP13.22-P-1351Z
₽ AP	Replace fuel filter		AP47.20-P-0780PV
₽ AP	Replace activated charcoal filter		AP83.00-P-8382P
	Every 2 years		
	Replace dust filter		AP83.00-P-8381P
₩AP	Replace brake fluid		AP42.00-P-4280BP
₩ AP	Check body for paint damage by Service Advisor		AP98.00-P-9850BA
₩ AP	Check chassis and supporting body parts for damage and corrosion by Service Advisor		AP00.20-P-0090BA
	Every 3 years		
₩ AP	Sliding/pop-up roof: clean sliding rails and sliders		AP77.20-P-7731A
	At approx. every 150,000 mi/250,000 km or 15 years		
₽ AP	Replace coolant		AP20.00-P-2080A
	Replace spark plugs		
⊯ AP	At approx. every 80,000 mi/129,000 km or 5 years Engine 271 (M.Y. 2003)		AP15.10-P-1580A
⊯ AP	At approx. every 100,000 mi/160,000 km or 5 years		AP15.10-P-1580A