

AP00.20-U-1208BAD SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

## MODEL 209

AMG models only

## Passenger cars Model Year 2008

USA



Customer:			Repair order n	umber:		
First visit	at 1,000 - 3,000 miles		Performed	YES NO		
Rear axle differential fluid replaced	during first visit (CLK63 AMG Black Series only)		Performed	YES NO		
Tire Rotation (non staggered width wheel setup only)	Performed in accordance manufacturer's recommo		Tires rotated	YES NO		
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage inflation pressure	and correct tire	Tires inspected	YES NO		
Current mileage reading:			Oil grade/visco	sity:		
Additional notes:						
Service work to be performed as advised by Completion date: Confirm work has been performed by signing service advisor: below:						
1st A service at 10,000 miles o	r 1 year, then every 20,000	miles or 2 years				
1st B service at 20,000 miles o	r 2 years, then every 20,000	) miles or 2 years				
Determine "Additional Work (check if applicable)	" needed, if any. Refer to ",	Additional work" sec	tion			
once at:	10,000 mi or 1 year		every:	2 years		
	40,000 mi			5 years		
	150,000 mi			40,000 mi		
at either:	40,000 mi or 4 years					
	50,000 mi or 4 years					
	60,000 mi or 5 years					
	150,000 mi or 15 years					

## **i** See last page for "Additional Work".

Additional flat rates apply for procedures marked with FAP

Completed 🗵		A-Service	O B-Service	Not OK	
	Interior	$\downarrow$	Ļ	$\downarrow$	
	interior				
	Reset maintenance counter in instrument cluster	$\boxtimes$	$\otimes$		AP00.20-P-0042PIT
	Function check				
	Horn, high beam flasher, hazard warning flashers, turn signals	$\boxtimes$	$\otimes$		
	Warning/indicator lamps, illumination and interior lighting	$\boxtimes$	$\otimes$		AP54.30-P-5452C
	Windshield wipers, windshield washer system, headlamp cleaning system	$\boxtimes$	$\otimes$		AP82.30-P-8252A
	Check seat belts for damage and proper function		$\otimes$		AP91.40-P-9150P
	Check parking brake (function test only)		$\otimes$		
	Wheels, brakes				
	Check thickness of brake pads, front and rear	$\boxtimes$	$\otimes$		AP42.10-P-4253A
	Inspect tires for damage and condition	$\boxtimes$	$\otimes$		AP40.10-P-4051Z
	Measure tread depth, enter in mm:		$\otimes$		AP40.10-P-4051Z
	LF         RF         LR         RR           outside		2		
	Correct tire inflation pressure and enter in bar or psi. LF RF LR RR bar/psi:		$\otimes$		
	bar/psi:				
	Leakage - Major components Check for chafe marks, line routing, dama- ged components in the event of leakage, determine cau- se and perform repair via separate work or- der		8		AP00.20-P-0053BA
	Check condition of front axle ball joints and rubber boots		$\otimes$		AP33.20-P-3353BP
	Check condition of steering mechanical components and rubber boots		$\otimes$		AP46.00-P-4653F
	Engine compartment				
	Leakage - Major components Check for chafe marks, line routing, dama- ged components in the event of leakage, determine cau- se and perform repair via separate work or- der		8		AP00.20-P-0053BA
	Check condition of poly-V-belt		$\otimes$		
	Check catch, safety catch and hinges on en- gine hood for proper operation.	$\boxtimes$	$\otimes$		
	Replace dust filter		$\otimes$		AP83.00-P-8381P
	Engine oil and filter change	X	$\otimes$		AP18.00-P-0101GZ

Completed 🖂		A-Service	O B-Service	Not OK	
↓		Ļ	Ļ	$\downarrow$	
	Check fluid level, correct as required i If there is a loss of fluid, determine cau- se and perform repair via separate work or- der				
	Brake system	X	$\otimes$		AP42.10-P-4210Z
	Power steering		$\otimes$		AP46.00-P-4611P
	Battery, check and correct fluid level	$\boxtimes$	$\otimes$		AP54.10-P-5410A
	Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.		⊗		
	Windshield washer system (incl. summer/winter cleanser)	$\boxtimes$	$\otimes$		AP82.35-P-8210P
	Vehicle front/rear				
	Check wiper blade condition	$\boxtimes$	$\otimes$		AP82.30-P-8253G
	Check and correct headlamp setting		$\otimes$		AP82.10-P-8260P
	Trunk				
	Check trunk lighting	$\boxtimes$	$\otimes$		
	Check TIREFIT tire sealant expiration date and enter here Replace TIREFIT if necessary subject to separate repair order		8		AP40.10-P-4054R
	Additional Work				
Completed 🗵	Perform:			Not OK	
$\downarrow$	0 · · · · · · · · · · · · · · · · · · ·	Ļ		$\downarrow$	
~~·~	Once at first service at 10,000 mi or 1 year:	_		П	
AP	Parking brake - Adjust cable slack Once at 40,000 mi:				AP42.20-P-4262P
<u>-</u>	Once at 40,000 mi:				
₩ AP	Automatic transmission - oil and filter change				AP27.00-P-2702W
F AP □	change				AP27.00-P-2702W
FRAP					AP27.00-P-2702W AP35.00-P-3501QBS
	change At every 40,000 mi: Replace rear axle differential fluid				
	change At every 40,000 mi: Replace rear axle differential fluid (CLK63 AMG Black Series only)				
₩ AP	change At every 40,000 mi: Replace rear axle differential fluid (CLK63 AMG Black Series only) At every 40,000 mi or 4 years:				AP35.00-P-3501QBS
₩ AP	change At every 40,000 mi: Replace rear axle differential fluid (CLK63 AMG Black Series only) At every 40,000 mi or 4 years: Replace air cleaner filter element				AP35.00-P-3501QBS
	changeAt every 40,000 mi:Replace rear axle differential fluid (CLK63 AMG Black Series only)At every 40,000 mi or 4 years:Replace air cleaner filter elementAt every 50,000 mi or 4 years:				AP35.00-P-3501QBS AP09.10-P-0980GZS
	changeAt every 40,000 mi:Replace rear axle differential fluid (CLK63 AMG Black Series only)At every 40,000 mi or 4 years:Replace air cleaner filter elementAt every 50,000 mi or 4 years:Check condition of driveshaft flex discs				AP35.00-P-3501QBS AP09.10-P-0980GZS
Image: AP     □       Image: AP     □       Image: AP     □       Image: AP     □       Image: AP     □	changeAt every 40,000 mi:Replace rear axle differential fluid (CLK63 AMG Black Series only)At every 40,000 mi or 4 years:Replace air cleaner filter elementAt every 50,000 mi or 4 years:Check condition of driveshaft flex discsAt every 60,000 mi or 5 years:Replace activated charcoal filter (if equipped)				AP35.00-P-3501QBS AP09.10-P-0980GZS AP41.10-P-4152Z
→ AP	changeAt every 40,000 mi:Replace rear axle differential fluid (CLK63 AMG Black Series only)At every 40,000 mi or 4 years:Replace air cleaner filter elementAt every 50,000 mi or 4 years:Check condition of driveshaft flex discsAt every 60,000 mi or 5 years:Replace activated charcoal filter (if equipped)				AP35.00-P-3501QBS AP09.10-P-0980GZS AP41.10-P-4152Z AP83.00-P-8382P
	changeAt every 40,000 mi:Replace rear axle differential fluid (CLK63 AMG Black Series only)At every 40,000 mi or 4 years:Replace air cleaner filter elementAt every 50,000 mi or 4 years:Check condition of driveshaft flex discsAt every 60,000 mi or 5 years:Replace activated charcoal filter (if equipped)Replace spark plugs (Engine 156)				AP35.00-P-3501QBS AP09.10-P-0980GZS AP41.10-P-4152Z AP83.00-P-8382P

	Completed 🗵	Perform:	Yes	Not OK	
	Ļ		$\downarrow$	$\downarrow$	
		Every 2 years:			
₩°AP		Replace brake fluid			AP42.00-P-4280BP
₩AP		Check body for paint damage <b>by service advisor</b>			AP98.00-P-9850BA
₩ <b>₽</b> AP		Check chassis and supporting body parts for damage and corrosion <b>by service advisor</b>			AP00.20-P-0090BA
		Every 5 years:			
₩°AP		Tilting/sliding roof - clean slide rails and slide shoes			AP77.20-P-7731A
		Vehicle over 150,000 mi:			
		Check if all fluid levels and changes are up- dated			
₩P		Transmission			
₩AP		Rear axle			
		Check if air, fuel, ventilation filters are up- dated			
₩AP		Engine air filter			
₩P		Fuel filter			
⊯≊ AP		Dust filter			
⊯≊ AP		Activated charcoal filter (if equipped)			
		Check integrity of engine, mechanical co- monents			
₩AP		Perform compression test (hot and cold) Refer to BE01.00-Z-9999AZ			
⊯≊ AP		Perform leak down test (hot and cold)			AP00.20-P-0053BA
₩°AP		Check spark plugs			
₩°AP		Exhaust system hangers and leaks			
		Check damaged / worn drivetrain parts			
₩AP		Front wheel bearing play			
₩°AP		Rear wheel bearing play			
⊯ AP		Axle joint play			
₩ <b>°</b> AP		Driveshaft flexible disks			
₩ĨAP		Tie rod and drag link joints			