

AP00.20-U-1208JC SERVICE SHEET for Mercedes-Benz Maintenance System (USA) 19.6.06

MODEL 216

except AMG models and CL600

Passenger cars Model Year 2007

Model 216



Customer:		Repair order number:		
First visit	at 1,000 - 3,000 miles	Performed	YES NO	
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO	
Current mileage reading:				
Service work to be performed as advised by Completion date: service advisor:		Confirm work has been performed by signing below:		

i

US Service 4-20 apply to "Additional work" items only.

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2

Perform each service as described.

US Service		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
1	US Service	first at 26,000 mi or 2 years;	after first every 26,000 mi or 2 years	
\downarrow	2 ↓		Not OK ↓	
		Interior		
	0	Reset service indicator in instrument cluster		AP00.20-P-0042SX
	0	Night View Assist camera - clean windshield behind the camera cover		AP54.30-P-5431SX
		Function test		
	0	Check parking brake (function test only)		AP42.00-P-4292SX
	0	Horn		
	0	Warning/indicator lamps, illumination and interior lighting		AP54.30-P-5452C
	0	Windshield wipers, windshield washer system, headlamp cleaning system		AP82.30-P-8252SX
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150SX
		Wheels, brakes		
	0	Inspect tires for damage and splits, measure tread depth, enter in mm: LF RF LR RR outside		AP40.10-P-4051SX
		inside		
		Check front brake pads for lining thickness (remove right front wheel)		
	0	Remove and install wheels	_	AP40.10-P-4050SX
	Ö	Check front/rear brake pads for lining thickness		
	0	Check condition/thickness of front/rear brake discs		
	0	Correct tire inflation pressure and enter in bar or psi. LF RF LR RR		
		bar/psi:		
		Underside of vehicle		
	0	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053SX
	0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353SX
	0	Inspect condition of driveshaft flexible discs		AP41.10-P-4152SX
	0	Inspect play of tie rod and drag link joints, inspect rubber boots		AP46.00-P-4653SX

US Service	US Service		Not OK	
1	2 ↓		1	
i de	Poi	Vehicle front/rear	· .	
	0	Check and correct headlamp setting		AP82.10-P-8260SX
	0	Check wiper blade condition		AP82.30-P-8253SX
		Trunk		
	0	Check auxiliary battery condition using "Midtronics MCR 717" Tester. Attach "Midtronics MCR 717" Test Report print out here.		AP54.10-U-5453A
	0	Correct inflation pressure in spare tire and enter in bar or psi. bar/psi:		
	0	Check trunk lighting		
		Engine compartment		
	0	Leakage - Major components Check for chafe marks, line routing, damaged components iln the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053SX
	0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851SX
	0	Check condition of poly-V-belt		
		Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order		
	0	Starter battery, check and correct fluid level; Check battery condition using "Midtronics MCR 717" Tester. Attach "Midtronics MCR 717" Test Report print out here.		AP54.10-U-5453A
	0	Brake system		AP42.10-P-4210SX
	0	Power steering		AP46.00-P-4611SX
	0	Active Body Control		AP32.50-P-3213SX
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210SX
		Additional Work		
Co	mpleted 🗵		Not OK	
US Sei	vice 3	every 13,000 mi or 1 year:	\	
		Engine compartment		
		Engine - oil and filter change		AP18.00-P-0101SX

Completed ⊠	I		Not OK	
↓			↓	
US Service 4	every 2 years:			
	Check bodywork for paint work damage by service advisor			AP98.00-P-9850SX
	Underside of vehicle			
	Chassis and load-bearing body components: Check for damage and corrosion by service advisor			AP00.20-P-0090SX
	Engine compartment			
	Replace brake fluid			AP42.00-P-4280SX
US Service 5	every 26,000 mi or 2 years:			
	Passenger compartment			
	Replace combination filter			AP83.00-P-8384SX
US Service 6 & 7	not applicable			
US Service 8	every 52,000 mi or 4 years:			
	Engine compartment			
	Replace engine air-cleaner insert			AP09.10-P-0980SX
US Service 9 & 10	not applicable			
US Service 11	every 143,000 mi or 15 years:			
	Passenger compartment			
	Replace fuel filter			AP47.20-P-0780SX
US Service 12 Engine 273	every 91,000 mi or 5 years: Engine compartment			
	Replace spark plugs			AP15.10-P-1580SX
US Service 13	every 143,000 mi or 15 years:			
	Engine compartment			
	Replace coolant			AP20.00-P-2080SX
US Service 14 - 19	not applicable			
US Service 20	once at 39,000 mi:			
	Underside of vehicle			
	Automatic transmission - oil and filter change			AP27.00-P-2702W
	Vehicle over 143,000 mi:			
	Check if all fluid levels and changes are updated			
 ⊯AP □	Transmission			
 ⊯AP □	Rear axle			
	Check if air, fuel, ventilation filters are updated			
 ⊯AP □	Engine air filter			
FAP □	Fuel filter			
I⊯AP □	Combination filter			
	Compilation med	L		

	Completed ⊠	Perform:	Yes	Not OK	
	\		↓	↓	
		Check integrity of engine, mechanical comonents			
₩ÃΡ		Perform compression test (hot and cold) Refer to BE01.00-Z-9999AZ			
β≅AP		Perform leak down test (hot and cold)			AP00.20-P-0053SX
F≆AP		Check spark plugs			
₩ŶΑP		Exhaust system hangers and leaks			
		Check damaged / worn drivetrain parts			
F≆AP		Front wheel bearing play			
₩FAP		Rear wheel bearing play			
FAP		Axle joint play			
FAP		Driveshaft flexible discs			
₩ŶΑP		Tie rod and drag link joints			