

Service

AP00.20-U-1208G Service Sheet for Mercedes-Benz Maintenance System (USA) 15.03.04

MODEL 163

Light Truck Model Year 2005

USA

Model 163



Customer:		Repair order number:					
First visit	at 1,000 - 3,000 miles	Performed	YES	NO			
Tire Rotation	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES	NO			
Tire Inspection	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES	NO			
Current mileage reading:		Oil grade/viscosity: _					
Additional notes:							
	med as advised by Completion o		nfirm work has bee ning below:	n performed by			
service advisor:	med as advised by Completion of Completion o	sig		n performed by			
service advisor: 1st A service at 13,0		signification si		n performed by			
1st A service at 13,0	00 miles or 1 year, then every 26,000 m	signiles or 2 years	ning below:	n performed by			
1st A service at 13,0	00 miles or 1 year, then every 26,000 m	signiles or 2 years	ning below:	n performed by			
1st A service at 13,0 1st B service at 26,0 Determine "Addition	00 miles or 1 year, then every 26,000 m 00 miles or 2 years, then every 26,000 al work" needed, if any. Refer to "Addi	signiles or 2 years miles or 2 years tional Work" secti	ning below:	n performed by			
1st A service at 13,0 1st B service at 26,0 Determine "Addition (check if applicable)	00 miles or 1 year, then every 26,000 m 000 miles or 2 years, then every 26,000 al work" needed, if any. Refer to "Addit 52,000 mi or 4 years	signiles or 2 years miles or 2 years tional Work" secti	ion 2 years	n performed by			
1st B service at 26,0 Determine "Addition (check if applicable)	00 miles or 1 year, then every 26,000 m 00 miles or 2 years, then every 26,000 al work" needed, if any. Refer to "Addir 52,000 mi or 4 years 65,000 mi or 5 years	signiles or 2 years miles or 2 years tional Work" secti	ion 2 years 4 years	n performed by			
1st A service at 13,0 1st B service at 26,0 Determine "Addition (check if applicable)	00 miles or 1 year, then every 26,000 m 00 miles or 2 years, then every 26,000 al work" needed, if any. Refer to "Addir 52,000 mi or 4 years 65,000 mi or 5 years	signiles or 2 years miles or 2 years tional Work" secti	ion 2 years 4 years 5 years	n performed by			

completed	$\downarrow \\$	A-Servic	e 🗆	0	B-Service	Not O.F	ζ .
		Interior					
		Reset maintenance counter in instrument cluster	X	8			
		Replace dust filter		\otimes			AP83.00-P-8381GH
		Function check					
		Warning/indicator lamps, illumination and interior lighting	X	\otimes			
		Throttle cable: operate accelerator cable slowly by foot through full range travel. i Observe smoothness of operation if roughness is detected, replace throttle cable.		8			AP30.10-P-3024GH
		Windshield wipers, rear window wiper, windshield/rear window washer system	X	8			AP82.35-P-8252GH
		Headlamp cleaning system	X	\otimes			
		Check seat belts for damage and proper function		8			AP91.40-P-9150GH
		Check parking brake (function test only)		8			AP42.00-P-4290GH
		Wheels, brakes					
T T		Check front brake pads for lining thickness (remove 1 front wheel)	X				AP42.10-P-4251GH
		Check brake pad thickness front/rear		\otimes			AP42.10-P-4251GH
		Check condition/thickness of brake discs front/rear		8			AP42.10-P-4251GH
		Check tires for damage and condition	X	\otimes			AP40.10-P-4051Z
		Measure tread depth, enter in mm: LF RF LR RR outside		8			AP40.10-P-4051Z
		Correct tire inflation pressure including spare	\boxtimes				

completed	$\downarrow \\$	A-Service	• □ ↓	O B-Service	Not O.M	
		Underside of vehicle Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		⊗		AP00.20-P-0053GH
		Check condition of front axle ball joints and rubber boots		8		AP33.20-P-3353GH
		Check condition of rear axle ball joints and rubber boots		8		AP35.20-P-3555GH
		Check condition of steering's mechanical components and rubber boots		8		AP46.00-P-4653GH
		Engine compartment				
		Visually inspect the lower power steering hose connection at the radiator. i If found to be leaking, replace lower power steering hose with separate work order	X	⊗		AP46.25-P-4645GH
		Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		⊗		AP00.20-P-0053GH
		Engine oil and filter change	\boxtimes	\otimes		AP18.00-P-0101GH
		Lubricate joints on throttle control, check operation and condition		8		AP30.10-P-3022GH
		Check catch, safety catch and hinges of engine hood for proper operation. Replace components with even the slightest malfunction.	X	⊗		AP88.40-P-8821GH
		Check condition of poly-V-belt		\otimes		AP13.22-P-1351GH
		Check and correct fluid level I If there is a loss of fluid, determine caus and perform repair via separate work or				
		Engine cooling system, antifreeze and corrosion protection	\boxtimes	8		AP20.00-P-2010GH
		Power steering		\otimes		AP46.00-P-4611BB
		Brake system	×	\otimes		AP42.10-P-4210Z

completed	\downarrow	A-Service	□ ↓	O B-Service	Not O.K	•
		If so equipped: Battery, wet cell Check battery acid level, replenish	×	8		AP54.10-P-5410A
		Additionally, check battery condition using "Midtronics MCR 717" Tester	\boxtimes	\otimes		AP54.10-U-5453A
		Windshield washer, incl. rear window washer (where applicable)	\boxtimes	8		AP82.35-P-8210GH
		Additional Work				
completed	⊠ I	Perform:	Yes I		Not O.K	
	ţ	Every 52,000 mi or 4 years:	ţ		ţ	
I≆ AP	П		П			
AF	<u> </u>	Engine air filter: replace element				
		Every 65,000 mi or 5 years:				
r≆ AP		Replace fuel filter				AP47.20-P-0780GH
		Every 143,000 mi or 15 years:				
i≆° AP		Replace coolant (water/anticorrosion/antifreeze)				AP20.00-P-2080GH
		Replace spark plugs				
i≈ AP		Every 91,000 mi or 5 years: As of M.Y. 2000				AP15.10-P-1580GH
		Every 2 years:				
I≆ AP		Replace brake fluid				AP42.00-P-4280GH
r≆ AP		Retighten bolts of front axle carrier				AP33.10-P-3373GH
r≆ AP		Retighten bolts of rear axle carrier				AP35.10-P-3573GH
r≆ AP		Check body for paint damage by Service Advisor				AP98.00-P-9850BA
p≆ AP		Check chassis and supporting body parts for damage and corrision by Service Advisor				AP00.20-P-0090GH
		Every 4 years:				
r≆ AP		Replace retaining strap rear axle carrier				

complete	d 🗵	Perform:	Yes	Not O.K. ↓
i≆° AP		Every 5 years: Tilt/sliding roof: clean sliding rails and sliders		AP77.20-P-7730GH
		Vehicle over 143,000 mi: Check if all fluid levels and changes are updated		
r≆ AP		Transmission		
r≆ AP		Rear axle		
r≆ AP		Front axle (if applicable)		
r≆ AP		Transfer case (if applicable)		
		Check if air, fuel, ventilation filters are updated		
F AP		Engine air filter		
r≆ AP		Fuel filter		
r≆ AP		Combination / dust filter (if applicable)		
r≆ AP		Activated charcoal filter (if applicable)		
		Check integrity of engine, mechanical components		
r≆ AP		Perform compression test (hot and cold)		☐ BE01.00-Z-9999AZ
r≆ AP		Perform leak down test (hot and cold)		AP00.20-P-0053GH
r≆ AP		Check spark plugs		
r≆ AP		Exhaust system hangers and leaks		
		Check damaged / worn drivetrain parts		
r≆ AP		Front wheel bearings play		
r≆ AP		Rear wheel bearings play		
F AP		Axles joints play		
r≆ AP		Flexible discs		
I≆ AP		Tie rod and drag link joints		