

AP00.20-U-1208RC SERVICE SHEET for Mercedes-Benz Maintenance System (USA) 25.4.07

MODEL 251

except diesel models

Light Truck Model Year 2008

Model 251



Customer:		Repair order number:		
First visit	at 1,000 - 3,000 miles	Performed	YES NO	
Tire Rotation (non-staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO	
Tire Inspection (staggered and non-staggered width wheel set up)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO	
Current mileage reading:		Oil grade/viscosity:		
Additional notes:				
Service work to be performed as service advisor:	advised by Completion date:	Confirm work below:	has been performed by signii	ng

i

US Service 4 through US Service 20 apply to "Additional work" items only.

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2

Perform each service as described.

US Service		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
1	US Service	first at 26,000 mi or 2 years;	after first every 26,000 mi or 2 years	
↓	2 J		Not OK ↓	
		Interior	·	
	0	Reset service indicator in instrument cluster		AP00.20-P-0042RT
		Function test		
	0	Horn		
	0	Warning/indicator lamps, illumination and interior lighting		AP54.30-P-5452C
	0	Windshield wipers, windshield washer system, headlamp cleaning system		AP82.30-P-8252RT
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150RT
	0	Battery, check battery condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here.		
	0	Check parking brake (function test only)		
		Wheels, brakes		
	0	Inspect tires for damage and splits, measure tread depth, record in mm: LF RF LR RR outside		AP40.10-P-4051RT
	0	Check front/rear brake pads for lining thickness		AP42.10-P-4253A
	0	Correct tire inflation pressure and enter in bar or psi. LF RF LR RR bar/psi:		
		Underside of vehicle		
' '	' 0	Leakage - Major components Check for chafe marks, line routing, damaged components iln the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053RT
	0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353RT
	0	Check rear axle ball joints for play, check rubber boots		AP35.20-P-3555RT
	0	Inspect play of tie rod and and drag link joints, inspect rubber boots		AP46.00-P-4653RT
io		Vehicle front/rear		
	0	Check wiper blade condition		AP82.30-P-8253G
	\cap	Check and correct headlamp setting	П	AP82.10-P-8260RT

US Service	US Serv			Not OK	
1 1		2 ↓		↓	
		•	Engine compartment	•	
		0	Leakage - Major components Check for chafe marks, line routing, damaged components in the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053RT
		0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851RT
		0	Check condition of poly-V-belt		
		0	Clean water drain in air/water duct		AP83.10-P-8339M
			Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order		
		0	Brake system		AP42.10-P-4210RT
		0	Power steering		AP46.00-P-4611RT
		0	Windshield washer system		AP82.35-P-8210RT
			(incl. summer/winter cleanser)		
		_	Additional Work		
Co	mpleted	⊠		Not OK ↓	
US Se	rvice 3		every 13,000 mi or 1 year:		
			Engine compartment		
			Engine - oil and filter change		AP18.00-P-0101RTC
US Se	rvice 4		every 2 years:		
			Check bodywork for paint work damage by service advisor		AP98.00-P-9850RT
			Underside of vehicle		
			Chassis and load-bearing body components: Check for damage and corrosion by service advisor		AP00.20-P-0090RT
			Engine compartment		
			Replace brake fluid		AP42.00-P-4280RT
US Se	rvice 5		every 26,000 mi or 2 years:		
			Passenger compartment		
			Replace combination filter		AP83.00-P-8384RT
US Servi	ce 6 and 7	7	not applicable		
US Se	rvice 8		every 52,000 mi or 4 years: Engine compartment		
			Replace engine air-cleaner insert		AP09.10-P-0980RTC
US Se	rvice 9		not applicable		
US Ser	vice 10		every 3 years:		
			Panorama sliding roof: Clean and lubricate guide mechanism		AP77.20-P-7732RT

Completed ⊠		Not 0	OK
↓		↓	
US Service 11	every 143,000 mi or 15 years: Passenger compartment		
	Replace fuel filter		AP47.20-P-0780RT
US Service 12	every 91,000 mi or 5 years: Engine compartment		
	Replace spark plugs	Engine 272:	AP15.10-P-1580RTC
US Service 13	every 143,000 mi or 15 years:		
	Engine compartment		
	Replace coolant		AP20.00-P-2080RTC
US Service 14-19	not applicable		
US Service 20	once at 39,000 mi:		
	Underside of vehicle		
	Automatic transmission - oil and filter change		AP27.00-P-2702W
	Vehicle over 143,000 mi:		
	Check if all fluid levels and changes are updated		
⊯AP □	Transmission]
FAP □	Rear axle]
FAP □	Front axle (if applicable)]
⊯ AP □	Transfer case (if applicable)	С]
	Check if air, fuel, ventilation filters are updated		
⊯AP □	Engine air filter]
FAP □	Fuel filter]
FAP □	Combination filter]
	Check integrity of engine, mechanical comonents		
F AP □	Perform compression test (hot and cold) Refer to BE01.00-Z-9999AZ]
F AP □	Perform leak down test (hot and cold)		AP00.20-P-0053RT
FAP □	Check spark plugs]
⊯ AP □	Exhaust system hangers and leaks	С]
	Check damaged / worn drivetrain parts		
⊯ AP □	Front wheel bearing play]
⊯ AP □	Rear wheel bearing play]
⊯ AP □	Axles joint play]
⊯ AP □	Driveshaft flexible discs]
⊯ AP □	Tie rod and drag link joints]